



733



1504-2-11



1504-2-31



ISO 9001:2015

# SR CABLES

## PVC insulated cable for motor vehicles, single core general wiring cables



### TECHNICAL INFORMATION

Application	Motor Vehicles General Wiring	Insulation Material	PVC T1 1
Reference Standards	SLS 412 : PART1, ISO 6722	Color of Insulation	Black, Blue, Brown, Green, Grey, Orange, Pink, Purple, Red, White, Yellow
Voltage Rating	100 V Max		
Number of Cores	Single		
Conductor Class	Class 5 Annealed Copper		

Nominal Cross Sectional Area of Conductor (mm <sup>2</sup> )	Construction of Conductor (mm)	Approx Diameter of Conductor (mm)	Radial Thickness of Insulation (mm)	Maximum Overall Diameter (mm)	Max. d.c Resistance at 20 °C Ohms / km	Approx Wight kg / km
0.65	9/0.30	1.1	0.6	2.5	29.35	11.7
1.0	32/0.20	1.3	0.6	2.7	18.8	15.5
2.00	28/0.30	1.9	0.6	3.3	9.42	27.9
2.5	35/0.30	2.1	0.7	3.6	7.54	34.9
3.0	44/0.30	2.3	0.8	4.1	6.0	43.4
4.5	65/0.30	2.8	1.0	5.1	4.06	64.2



## S. R. CABLES (PVT) LTD

05, Sangamitta Mawatha, Colombo 13, Sri Lanka

T | (+94) 011 2421 373 / 2341 584

F | (+94) 011 2323 304 / 2454 627

E | [sales@srcables.lk](mailto:sales@srcables.lk)

[www.srcables.lk](http://www.srcables.lk)